

PROVENCE WAX CLASSIC WALNUT

GENERAL CHARACTERISTICS:

A special WAX FINISH FOR WOOD suited for all common applications on wood, either raw or treated with nitro, polyurethane, synthetic or water-based treatment.

The product is composed of IRON OXIDE AND INORGANIC PIGMENT DYES; hence it has good light resistance.

Therefore, the product can be employed outside, except where water could rapidly spoil the finish.

APPLICATION:

MIX THE PRODUCT WELL BEFORE USE.

With a brush or cloth, after adjusting viscosity with the proper thinners:

TURPENTINE ESSENCE, TURPENTINE OIL in varying percentage, according to how the product is used (as wax on raw wood, on primed wood or wax filler).

As a starting point, an optimal thinning is 40 %.

Apply a thin and uniform layer, wait at least 8 - 10 hours and polish with a brush or cotton cloth.

APPEARANCE COLORED PASTE

SCENT UNIQUE

DRYING about 24 hours at 20° C

BRUSHING about 24 hours at 20° C

POTENTIAL YIELD about 8/10 sqm/Lt

USE AND WARNING

The product can be used on most surfaces, either raw or primed with nitro or water-based colors.

IMPORTANT:

The product has elevated staining properties. Therefore, it is recommended to test the product if the surface has already been mordanted.

- The information contained in this section is based on our experience.
- The information herein contained does not constitute a binding warranty.
- REV. 8/2007